

FT 4

Tinned Copper
600V

ElectroCom®



14 AWG FT4 600V - Overall Shielded Multi-Conductors

Multi	Part No.	Conductor Count	Insulation Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius	
			in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm
			5151402TFT4	2	0.015	0.38	0.262	6.7	48	72	68	31
5151403TFT4	3	0.015	0.38	0.278	7.1	66	98	102	46	3.9	99	
5151404TFT4	4	0.015	0.38	0.305	7.7	84	124	137	62	4.3	108	
5151405TFT4	5	0.015	0.38	0.335	8.5	98	146	171	77	4.7	119	
5151407TFT4	7	0.015	0.38	0.400	10.2	135	201	239	108	5.6	142	
5151409TFT4	9	0.015	0.38	0.450	11.4	171	254	307	139	6.3	160	
5151415TFT4	15	0.015	0.38	0.559	14.2	284	422	512	232	7.8	199	
5151425TFT4	25	0.015	0.38	0.680	17.3	447	665	854	387	9.5	242	
5151430TFT4	30	0.015	0.38	0.779	19.8	546	813	1025	465	10.9	277	

Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 214/UL 444, Communication Cables (Type CMG)
- CSA C22.2 No. 210, Appliance Wiring Material (AWM I/II A/B)
- UL 13, Power Limited Circuit Cables (CL3)
- CSA C22.2 No. 2556 FT4, UL 1685 Vertical-Tray Flame Test
- IEEE 383 & 1202, ICEA T-30-520 (70,000 BTU/hr) Vertical Flame Test rated

Conductor	Stranded Tinned Soft Copper, ASTM B33
Insulation	Polyvinyl Chloride (SRPVC), 105°C
Shielding	Overall Shield with Tinned Copper Drain Wire
Jacket	Polyvinyl Chloride (PVC)

Applications

- For use in Class 2 circuits, communication, appliance wiring and power limited circuits where not subject to mechanical damage.
- For data processing and similar system connections and inter-connections installed under raised floors as per CE Code Part I 12-020 and NEC 725.154(A).
- For use indoors in raceways; dry or damp locations, exposed and concealed wiring.
- For Class 3 (NEC) circuits as described in NEC Article 725 and CE Code Part I.



SCAN or CLICK



Made In Canada



ElectroCables

515-06-A | 108