



10 AWG CIC 600V CSA FT4 TC

10 AWG	Part No.	Conductor Count	Bonding Conductor	Insulation Thickness		Jacket Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius		Ampacity
			AWG	in	mm	in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm	A
6XNAUS10-2CG-PV4	2/C	10	0.030	0.8	0.045	1.1	0.463	11.8	148	220	166	75	4.2	106	40	
6XNAUS10-3CG-PV4	3/C	10	0.030	0.8	0.045	1.1	0.489	12.4	191	284	249	113	4.4	112	40	
6XNAUS10-4CG-PV4	4/C	10	0.030	0.8	0.060	1.5	0.564	14.3	253	376	332	151	5.1	129	32	
6XNAUS10-5CG-PV4	5/C	10	0.030	0.8	0.060	1.5	0.615	15.6	304	452	415	188	5.5	141	32	
6XNAUS10-6CG-PV4	6/C	10	0.030	0.8	0.060	1.5	0.635	16.1	348	518	498	226	5.7	145	32	
6XNAUS10-7CG-PV4	7/C	10	0.030	0.8	0.060	1.5	0.667	16.9	393	585	581	264	6.0	152	28	
6XNAUS10-8CG-PV4	8/C	10	0.030	0.8	0.060	1.5	0.719	18.3	441	657	664	301	6.5	164	28	
6XNAUS10-9CG-PV4	9/C	10	0.030	0.8	0.060	1.5	0.745	18.9	486	723	747	339	6.7	170	28	
6XNAUS10-10CG-PV4	10/C	10	0.030	0.8	0.060	1.5	0.778	19.8	532	791	830	377	7.0	178	28	
6XNAUS10-11CG-PV4	11/C	10	0.030	0.8	0.060	1.5	0.808	20.5	577	858	913	414	7.3	185	28	
6XNAUS10-12CG-PV4	12/C	10	0.030	0.8	0.080	2.0	0.877	22.3	656	977	996	452	7.9	200	28	
6XNAUS10-15CG-PV4	15/C	10	0.030	0.8	0.080	2.0	0.976	24.8	797	1187	1245	565	8.8	223	28	
6XNAUS10-20CG-PV4	20/C	10	0.030	0.8	0.080	2.0	1.107	28.1	1026	1527	1660	753	10.0	253	28	
6XNAUS10-25CG-PV4	25/C	10	0.030	0.8	0.080	2.0	1.229	31.2	1254	1866	2075	941	11.1	281	24	
6XNAUS10-30CG-PV4	30/C	10	0.030	0.8	0.080	2.0	1.300	33.0	1473	2193	2490	1130	11.7	297	24	
6XNAUS10-40CG-PV4	40/C	10	0.030	0.8	0.080	2.0	1.455	37.0	1914	2848	3320	1506	13.1	333	24	
6XNAUS10-50CG-PV4	50/C	10	0.030	0.8	0.080	2.0	1.619	41.1	2356	3506	4150	1883	14.6	370	20	

Ampacity values based on CE Code Part I 2024, Table 2. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 239, Control and instrumentation cables (Type CIC)
- CSA C22.2 No. 38, Thermoset-insulated wires and cables (Type RW90)
- CSA C22.2 No. 230, Tray Cables (Standard TC rated. TC-ER Optional)
- CSA C22.2 No. 2556 FT4, UL 1685 Vertical-Tray Flame Test
- IEEE 383 & 1202, ICEA T-30-520 (70,000 BTU/hr) Vertical Flame Test rated
- -40°C Cold Bend and -40°C Cold Impact
- Sunlight Resistant, SUN RES. Low Acid Gas, AG14.

Conductor Stranded Soft Copper, ASTM B8

Insulation Cross-linked Polyethylene (XLPE)
CSA Type XL 90°C dry/wet 600V

Bonding Stranded Soft Copper, ASTM B8, XLPE Insulated (Green)

Jacket Low Acid Gas (LAG) Polyvinyl Chloride (PVC)

Colour Code 2C Black & White, 3C Black, Red & Blue, 4C Black, Red, Blue & White, 5C - 50C Black with White Numbers

Applications

- For use in raceways, ventilated, non-ventilated and ladder-type cable trays.
- For dry, damp or wet locations, in ceiling air-handling plenums and direct burial.
- For use in Hazardous locations: Zone 0 (intrinsically safe cables only), Zone 2, Zone 22 (per Section 18).

CUSTOM ORDER OPTIONS

