



14 AWG RW90 600V CSA FT4 TC-ER

14 AWG	Part No.	Conductor Count	Bonding Conductor	Insulation Thickness		Jacket Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius		Ampacity
			AWG	in	mm	in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm	A
	8201402BBG-P4E	2/C	14	0.030	0.8	0.045	1.1	0.372	9.5	87	129	68	31	3.3	85	25
	8201403BBG-P4E	3/C	14	0.030	0.8	0.045	1.1	0.392	10.0	108	160	102	46	3.5	90	25
	8201404BBG-P4E	4/C	14	0.030	0.8	0.045	1.1	0.427	10.8	130	193	137	62	3.8	98	20
	8201405BBG-P4E	5/C	14	0.030	0.8	0.045	1.1	0.465	11.8	154	230	171	77	4.2	106	20
	8201406BBG-P4E	6/C	14	0.030	0.8	0.045	1.1	0.481	12.2	175	261	205	93	4.3	110	20
	8201407BBG-P4E	7/C	14	0.030	0.8	0.045	1.1	0.504	12.8	197	293	239	108	4.5	115	17
	8201408BBG-P4E	8/C	14	0.030	0.8	0.060	1.5	0.574	14.6	237	352	273	124	5.2	131	17
	8201409BBG-P4E	9/C	14	0.030	0.8	0.060	1.5	0.594	15.1	259	385	307	139	5.3	136	17
	8201410BBG-P4E	10/C	14	0.030	0.8	0.060	1.5	0.619	15.7	281	418	342	155	5.6	142	17
	8201411BBG-P4E	11/C	14	0.030	0.8	0.060	1.5	0.641	16.3	303	451	376	170	5.8	147	17
	8201412BBG-P4E	12/C	14	0.030	0.8	0.060	1.5	0.664	16.9	325	484	410	186	6.0	152	17
	8201415BBG-P4E	15/C	14	0.030	0.8	0.060	1.5	0.739	18.8	393	585	512	232	6.7	169	17
	8201420BBG-P4E	20/C	14	0.030	0.8	0.080	2.0	0.878	22.3	536	798	683	310	7.9	201	17
	8201425BBG-P4E	25/C	14	0.030	0.8	0.080	2.0	0.970	24.7	649	965	854	387	8.7	222	15
	8201430BBG-P4E	30/C	14	0.030	0.8	0.080	2.0	1.025	26.0	755	1123	1025	465	9.2	234	15
	8201440BBG-P4E	40/C	14	0.030	0.8	0.080	2.0	1.142	29.0	968	1441	1367	620	10.3	261	15
	8201450BBG-P4E	50/C	14	0.030	0.8	0.080	2.0	1.266	32.2	1183	1760	1708	775	11.4	289	12

Ampacity values based on CE Code Part I 2021, Table 2. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 38, Thermoset-insulated wires and cables (Type RW90)
- CSA C22.2 No. 230, Tray Cables Extended Run
- CSA C22.2 No. 2556 FT4, IEEE 1202/UL 1685 Vertical-Tray Flame Test
- -40°C Cold Bend and -40°C Cold Impact
- SUN RES all colours

Conductor Stranded Bare Soft Copper, ASTM B8

Insulation Cross-linked Polyethylene Insulation (XLPE)
CSA Type XL 90°C dry/wet 600V

Jacket Low Acid Gas Polyvinyl Chloride (PVC)

Colour Code Black, White, Red and Blue or
Black with White printed number

Bonding Green Insulated Stranded Bare Soft Copper,
ASTM B8

Applications

- For wet and dry locations.
- For use in raceways, including cable trays, Ventilated, non-ventilated, ladder tray and direct burial.
- To be used for exposed and concealed wiring or where subjected to the weather.
- For Hazardous Locations Class I-Zone 0 Intrinsically safe Div. 2, Class II-Zone 2 Div. 2 and Class III-Div. 2.
- Cables marked TC-ER tray cable are permitted to transition between cable trays, and utilization equipment or devices as per CE Code Part I 12-2202 2) and 3).



CUSTOM ORDER OPTIONS

