



1 Conductor RW90 600V CSA FT4 TC

1C	Part No.	Conductor Size	Cable O.D.		Cable Weight		Max Pulling Tension		Resistance at 20°C	Ampacity
		AWG/kcmil	in	mm	lbs/Mft	kg/km	lbs	kg	Ω/Mft	A
	80501/OFT4	1/0	0.451	11.46	371	552	844	383	0.102	170
	80502/OFT4	2/0	0.495	12.57	466	693	1065	483	0.0811	195
	80503/OFT4	3/0	0.532	13.51	580	864	1343	609	0.0643	225
	80504/OFT4	4/0	0.596	15.14	723	1076	1692	767	0.0510	260
	80525OFT4	250	0.670	17.02	880	1310	2000	907	0.0432	290
	80535OFT4	350	0.807	20.50	1219	1814	2802	1271	0.0308	350
	80550OFT4	500	0.890	22.61	1594	2372	3997	1813	0.0216	430
	80560OFT4	600	1.030	26.16	2073	3085	4802	2178	0.0180	475
	80575OFT4	750	1.119	28.42	2586	3848	6002	2722	0.0144	535
	805100OFT4	1000	1.265	32.13	3415	5083	7995	3627	0.0108	615

Ampacity values based on CE Code Part I 2024, Table 2. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 38, Thermoset-insulated wires and cables (Type RW90)
- CSA C22.2 No. 230, Tray Cables (Type TC)
- CSA C22.2 No. 2556 FT4, IEEE 1202/UL 1685 Vertical-Tray Flame Test
- IEEE 383 & 1202, ICEA T-30-520 (70,000 BTU/hr) Vertical Flame Test rated
- -40°C Cold Bend and -40°C Cold Impact
- Sunlight Resistant, SUN RES all colours

Conductor Stranded Soft Copper, ASTM B8

Insulation Cross-linked Polyethylene (XLPE)
CSA Type XL 90°C dry/wet 600V

Applications

- For use in raceways, ventilated, non-ventilated and ladder-type cable trays.
- For dry, damp or wet locations and in ceiling air-handling plenums.
- For use in Hazardous locations: Zone 0 (intrinsically safe cables only), Zone 2, Zone 22 (per Section 18).



Made In Canada

CUSTOM ORDER OPTIONS

