



14 AWG CIC CONTROL 600V CSA FT4-ST1 TC-ER

14 AWG	Part No.	Conductor Count	Bonding Conductor	Insulation Thickness		Jacket Thickness		Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius		Ampacity
			AWG	in	mm	in	mm	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm	A
6XNAUS14-2CG-NHT	2/C	14	0.030	0.8	0.045	1.1	0.372	9.5	87	129	68	31	3.4	85	25	
6XNAUS14-3CG-NHT	3/C	14	0.030	0.8	0.045	1.1	0.392	10.0	107	160	102	46	3.5	90	25	
6XNAUS14-4CG-NHT	4/C	14	0.030	0.8	0.045	1.1	0.427	10.8	130	193	137	62	3.8	98	20	
6XNAUS14-5CG-NHT	5/C	14	0.030	0.8	0.045	1.1	0.465	11.8	154	229	171	77	4.2	106	20	
6XNAUS14-6CG-NHT	6/C	14	0.030	0.8	0.045	1.1	0.481	12.2	175	260	205	93	4.3	110	20	
6XNAUS14-7CG-NHT	7/C	14	0.030	0.8	0.06	1.5	0.504	12.8	197	292	239	108	4.5	115	17	
6XNAUS14-8CG-NHT	8/C	14	0.030	0.8	0.06	1.5	0.574	14.6	236	352	273	124	5.2	131	17	
6XNAUS14-9CG-NHT	9/C	14	0.030	0.8	0.06	1.5	0.594	15.1	258	384	307	139	5.3	136	17	
6XNAUS14-10CG-NHT	10/C	14	0.030	0.8	0.06	1.5	0.619	15.7	281	417	342	155	5.6	141	17	
6XNAUS14-11CG-NHT	11/C	14	0.030	0.8	0.06	1.5	0.641	16.3	303	450	376	170	5.8	147	17	
6XNAUS14-12CG-NHT	12/C	14	0.030	0.8	0.06	1.5	0.664	16.9	325	483	410	186	6.0	152	17	
6XNAUS14-15CG-NHT	15/C	14	0.030	0.8	0.06	1.5	0.739	18.8	392	584	512	232	6.7	169	17	
6XNAUS14-20CG-NHT	20/C	14	0.030	0.8	0.08	2.0	0.878	22.3	536	797	683	310	7.9	201	17	
6XNAUS14-25CG-NHT	25/C	14	0.030	0.8	0.08	2.0	0.970	24.7	648	964	854	387	8.7	222	15	
6XNAUS14-30CG-NHT	30/C	14	0.030	0.8	0.08	2.0	1.025	26.0	754	1121	1025	465	9.2	234	15	
6XNAUS14-40CG-NHT	40/C	14	0.030	0.8	0.08	2.0	1.146	29.1	970	1443	1367	620	10.3	262	15	
6XNAUS14-50CG-NHT	50/C	14	0.030	0.8	0.08	2.0	1.270	32.3	1185	1763	1708	775	11.4	290	12	

Ampacity values based on CE Code Part I 2021, Table 2. Correction factors may apply. Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- CSA C22.2 No. 38, Thermoset-insulated wires and cables (Type RW90)
- CSA C22.2 No. 239, Control and instrumentation cables (Type CIC)
- CSA C22.2 No. 230, Tray Cables Exposed Run (Type TC-ER)
- CSA C22.2 No. 2556 FT4-ST1 IEEE 1202/UL 1685
- NFPA 130 Smoke and Flame requirements.
- -40°C Cold Bend and -40°C Cold Impact
- Sunlight Resistant, Direct Burial, Low Acid Gas (AG14)

Conductor — Stranded Soft Copper, ASTM B8
Insulation — Cross-linked Polyethylene Insulation (XLPE)
 CSA Type XL 105°C dry, 90°C wet 600V
Bonding — Green Insulated Stranded Bare Soft Copper,
 ASTM B8

Jacket — Thermoplastic Low Smoke Zero Halogen
Colour Code — 2C Black & White, 3C Black, Red & Blue, 4C Black, Red, Blue & White, 5C - 50C Black with White Numbers

Applications

- For wet and dry locations.
- For use in raceways, including cable trays, Ventilated, non-ventilated, ladder tray and direct burial.
- To be used for exposed wiring where subjected to the weather.
- For Hazardous Locations (HL) Class I-Zone 0 Intrinsically safe Div. 2, Class II-Div. 2 and Class III-Div. 2 as per CE Code Part I J18-152, J18-254 and J18-354.
- Cables marked TC-ER tray cable are permitted for exposed runs as per CE Code Part I 12-2202 3) and 4).

