



14 AWG Control Cable CP-100

14 AWG	Part No.	Solid Conductor	Cable O.D.		Cable Weight		Max Pulling Tension		Min Bend Radius	
		Count	in	mm	lbs/Mft	kg/km	lbs	kg	in	mm
	82514-2C	2	0.472	12.0	78	116	66	30	3.8	96
	82514-3C	3	0.495	12.6	100	148	99	45	4.0	101
	82514-5C	5	0.580	14.7	149	221	164	75	4.6	118
	82514-6C	6	0.628	16.0	182	270	197	89	5.0	128
	82514-7C	7	0.656	16.7	204	304	230	104	5.2	133
	82514-8C	8	0.702	17.8	230	342	263	119	5.6	143
	82514-10C	10	0.754	19.2	275	409	329	149	6.0	153
	82514-12C	12	0.807	20.5	320	477	394	179	6.5	164
	82514-19C	19	0.994	25.2	494	736	624	283	8.0	202
	82514-20C	20	1.040	26.4	520	774	657	298	8.3	211
	82514-24C	24	1.148	29.2	614	913	788	358	9.2	233
	82514-28C	28	1.185	30.1	697	1037	920	417	9.5	241
	82514-37C	37	1.332	33.8	914	1360	1216	551	10.7	271

Dimensions and weights are nominal and subject to change without notice.

Specifications and Compliances

- Canadian Pacific Railway CP-100 600V Signal Cable
- -40°C Cold Bend and -40°C Cold Impact
- Sunlight Resistant and Halogen-free

Conductor Solid Bare Soft Copper Conductors, ASTM B3
Insulation Linear Low Density Polyethylene (LLDPE)
Jacket Linear Low Density Polyethylene (LLDPE)
Colour Code Standard Black Number Coded. Colour Code options available.

Applications

- For wet and dry locations.
- For installations in ducts or exposed wiring subjected to the weather.

